



HAL
open science

Adaptive Human Machine Interfaces in an Autonomous Vehicle

Céline Lemercier, Stéphanie Combettes, David Gomez Jauregui,
Marie-Christine Lagasquié-Schiex, Emmanuel Dubois, Nadine Couture

► **To cite this version:**

Céline Lemercier, Stéphanie Combettes, David Gomez Jauregui, Marie-Christine Lagasquié-Schiex, Emmanuel Dubois, et al.. Adaptive Human Machine Interfaces in an Autonomous Vehicle. Workshop on Explainable AI in Automated Driving: a User-Centered Interaction Approach in 11th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications (Automotive UI 2019), Sep 2019, Utrecht, Netherlands. pp.1-9. hal-03621807

HAL Id: hal-03621807

<https://hal.science/hal-03621807>

Submitted on 28 Mar 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Open Archive Toulouse Archive Ouverte

OATAO is an open access repository that collects the work of Toulouse researchers and makes it freely available over the web where possible

This is an author's version published in: <http://oatao.univ-toulouse.fr/25030>

To cite this version:

Lemercier, Céline and Combettes, Stéphanie and Gomez Jauregui, David and Lagasquie-Schiex, Marie-Christine and Dubois, Emmanuel and Couture, Nadine *Adaptive Human Machine Interfaces in an Autonomous Vehicle*. (2019) In: Workshop on Explainable AI in Automated Driving: a User-Centered Interaction Approach in 11th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications (Automotive UI 2019), 22 September 2019 (Utrecht, Netherlands).

Any correspondence concerning this service should be sent to the repository administrator:

tech-oatao@listes-diff.inp-toulouse.fr

Adaptive Human Machine Interfaces in an Autonomous Vehicle



Figure 1: AFP Illustration of PS (Passenger-Supervisor)

Céline Lemerrier
Toulouse 2 University
Toulouse, France
celine.lemerrier@univ-tlse2.fr

Marie-Christine Lagasquie
IRIT, UT3, Toulouse, France
Marie-Christine.Lagasquie@irit.fr

Stéphanie Combettes
IRIT, UT3, Toulouse, France
stephanie.combettes@irit.fr

Emmanuel Dubois
IRIT, UT3, Toulouse, France
Emmanuel.Dubois@irit.fr

David A. Gómez Jáuregui
Estia Institute of Technology
Bidart, France
d.gomez@estia.fr

Nadine Couture
Estia Institute of Technology
Bidart, France
n.couture@estia.fr

[Workshop on Explainable AI in Automated Driving: a User-Centered Interaction Approach](#), in 11th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications, September 22-25, 2019, Utrecht, Netherlands.

Abstract

In this position paper, we focus on human cockpit interaction using a human centered approach, that is to say the identification of important information that might be provided to drivers referring to the different levels of situation-awareness. We tackle the following question: "How to operate a dynamic delegation to the machine in the case of autonomous vehicles?".

Author Keywords

Human-AI interaction and collaboration; Multimodal Interaction and Interaction Design.

Introduction

Recently, autonomous vehicles have become a reality: many current production cars use features that enable better autonomy and driving control. In addition, future predictions foresee a considerable increase of the effective road capacity for autonomous and interconnected vehicles. However, a problem that has fewly been addressed is the interaction mechanisms used to operate a dynamic delegation from the machine to the human and vice versa depending on the context and situation. In this context, it

is important to investigate the field of Explainable Artificial Intelligence (XAI) since interpretability and transparency are key factors for increasing trust and security. In this position paper, we focus on human cockpit interaction, that is to say the identification of important information that might be provided to drivers referring to the different levels of situation-awareness. The question is "how to operate a dynamic delegation to the machine in the case of autonomous vehicles?" Two points are of great importance: first, to propose interaction mechanisms for a delegation in confidence, according to typologies of use cases and scenarios that will present in the following and second, to select the most critical information in real time and determine how to communicate it and interact with it.

State of the art

In vehicles with autonomous capacities, the role of the Artificial Intelligence (AI) part is to provide mechanisms capable to fuse the information, select important contextual cues, and recommends appropriate actions to the user according to the context [15]. In order to improve the user experience while interacting with an autonomous or semi-autonomous vehicle, it is necessary to facilitate user's acceptance to different levels of autonomous vehicle's mechanisms. Recent works have proposed the use of contextual cues to provide more efficient and trustworthiness interaction between user and vehicles. Amor et al. [3] proposed a context-aware agent-based system to assist drivers to determine where and when to refill fuel to their car while the vehicle is part of a vehicle's ad-hoc network. Al-Sultan et al. [2] designed a real-time detection of driver's behaviour using onboard sensors. This context-aware system is able to detect and classify the driver's behaviour into four categories as either normal, drunk, reckless, or fatigued; and this information can be shared with other vehicles for safety. The dynamic behavior model can capture the static and the temporal

aspects related to the behavior of the driver. Mobus et al. [27] designed a probabilistic machine-learning-based approach for the real-time prediction of the focus of attention and deficits of Situation Awareness (SA) using a Bayesian driver model as a driving monitor. This Bayesian driving monitor generates conditional expectations on the actions of the driver which are treated as evidence in the Bayesian driver model. Context-aware data used for this system are human behaviour manoeuvres (e.g., overtaking, turning), acceleration and distance between vehicles.

In human-vehicle interactions, there is a need of analysing and handling uncertainty to adjust to rapidly changing conditions. In these cases, the uncertainty of such sensor data can change rapidly over time and situations can sometimes be unpredictable [22]. In order to reduce these unexpected situations, Sanders et al. [31] proposed a shared control between the driver and vehicle sensors. In this approach, a trust-factor is calculated in real time for the vehicle driver and sensors help the human driver to drive their vehicle. Carlson et al. [8] presented a method to forecast direction and to adjust controller signals in order to cause the vehicle to travel in particular directions. Explainable models will also have to handle the loss of Situation Awareness (SA) that occurs when people oversee automation, limiting their ability to take back the control of the system and ultimately creating new types of failures [13]. In order to deal with high levels of uncertainty and unexpected situations, future XAI systems integrated to vehicles will need to be robust, adaptable to changing environment conditions or changing user behaviours, and be able to handle ambiguous and incomplete data [5].

Context & Scenario

Among the six levels of vehicle autonomy (from no automation to full automation) defined by the *National Highway*

Traffic Safety Administration (NHTSA) [1], we deal with the level 3: conditional automation. We remind that a level 3 vehicle can perform most driving tasks as it has both environmental detection and decisions capabilities. However the driver must be in the vehicle and must remain alert and ready to take control if necessary. In order to be clearer in the rest of this article, we define the following terms: 1) the Passenger-Supervisor (*PS*) is the "human" in the car that may be a passenger when the vehicle is in the autonomous mode or a driver (supervisor) when the vehicle can not manage a situation (see illustrations figures 1 and 2; 2) the Autonomous Vehicle (*AV*) is seen as Command System (*CS*) commanding the vehicle (*V*).

Before tackling the issues, let us describe a driving scenario of an autonomy level 3. The *AV* drives, i.e. the *CS* controls the driving of the vehicle. Meanwhile the *PS* goes about its business (occupation): he may read, look his emails, play, while being for example on a smartphone or a touch pad. This situation is going on until the *AV* detects a future problem in the driving control, a case that the *CS* cannot manage itself (e.g. defective sensor(s), very bad weather, etc.). At this moment the *CS* must give the control to the *PS* and the *PS* must be able to take back the control of the vehicle in a limited time. Thus the *PS* has taken the control (so drives) of the vehicle and the *AV* may be seen as "inactive". But once the problem is over, the *PS* may decide to stop driving and to give back the control of the vehicle to the *CS* of the *AV*. This transition has to be smoothly enough in order to keep the *PS* confidence in the *AV* and also for security reasons.

Through this short and simple scenario, several issues are raised, that in our knowledge, are not all solved. From this scenario, we may extract 4 phases of driving defined in figure 3. Phase 1 does not require more explanations as



Figure 2: Guetty Images
Illustration of PS
(Passenger-Supervisor)

this is the current main situation of driving. Phase 2 has been widely studied, so several solutions have been experimented in a real-life context. However from an ergonomic point of view, acceptability and attention of human are two important focus points. To accept to be in an *AV*, a passenger has to be confident and feel secured. Maintaining attention is necessary as the *AV* may give back the driving within a short time. The interest points here are the two last phases: phases 3 and 4. Some questions need to be tackled: in phase 3, at which moment can the Command System *CS* stop its vehicle control? In other words when does the *CS* know or deduce that the *PS* is in a position to take the control of the vehicle and that the *AV* does not need to be stopped for security reasons? Considering the phase 4, similar issues are raised: when will the *PS* accept to let go of the steering wheel? when will he/she have confidence in the *CS*? We address the issues of phases 3 and 4 according to a pluridisciplinary point of view that combine computer science (AI and HSI), humanities and social sciences (ergonomics).

Analysing the retrieving control of the vehicle

At levels 3-4, the driver will be required to take back control of the vehicle when he/she wishes or when the system requires it, due to external (on the road, weather-related) or internal (sensor failures) failures. The activity of the *PS* will therefore alternate periods of manual driving and periods of Non Driving-related Activities (NDRA) [9]. While an "elimination" of the accident risk associated with the human factors is likely to occur during autonomous driving periods, new safety risks related to critical transition periods for controlling driving activity are to be expected. All these steps define a transition from autonomous driving to manual driving, and vice versa, which must occur in less than 10 seconds. More critically for the level 3, the manoeuvre of manual control resumption by the *PS* could occur in

Phase 1

Non-autonomous steering: the *PS* drives the vehicle (i.e. the *CS* of the *AV* is not active).

Phase 2

Autonomous control: the *AV* drives and the *PS* is a passenger.

Phase 3

Transition from Autonomous to Non-autonomous Piloting: the *CS* of the *AV* gives the vehicle control to the *PS*.

Phase 4

Transition from Non-autonomous to Autonomous Piloting : *PS* gives the vehicle control to the *CS* of the *AV*.

Figure 3: The phases of driving

emergency, due to failure or inoperability of the autonomous system [26, 28, 24]. In an ethnocentric approach of human machine interaction, three factors have to be taken into account in order to limit the deleterious consequences of a misfit transition modalities between the Autonomous system of the Vehicule *AV* and the Human information Processing System. These factors are attentional switch, situation awareness and expertise. From this perspective, designing an adapted HSI means ensuring good communication from the human to the system and vice versa.

Autonomous driving and attentional switch

From the Level 4, *PS* will then be able to switch from a sort of Non-Driving Related Activity (NDRA) to another one while the autonomous system will supervise driving for several hours, and then s/he will have to take back control of his vehicle despite his total commitment to this side activity. The period of alternation between two tasks has been the subject of much work in selective attention, underlining its critical nature for humans. Laberge [21] was the first to demonstrate a deterioration in both the quality of the response and the response time of participants in a protocol requiring them to switch between two distinct tasks: the switch. It would be the consequence of attention overload caused on the one hand by the inhibition of the processing of the current task, and on the other hand by the activation of the processing of the alternating task. The vehicle of tomorrow has then offer to the *PS* the possibility of safely regaining control of the driving activity, regardless of the secondary activity (external to driving; e.g., film viewing) in which he will engage when the autonomous system supervises the driving activity. The first issue to solve is centered on the transition phase. The question asked here is how the *AV* will communicate with the *PS*: by which perceptual modality the "off/on" next status should be presented to ensure that the *PS* first detects, then identifies and finally

correctly reacts to the need of transition.

Autonomous driving and situation awareness

As already said, the autonomous driving phase could last several hours allowing *PS* to concentrate on a NRDA requiring strong workload. An intrinsic driver factor could also reinforce the already critical cost of alternation: loss of situational awareness [12, 23]. Recent studies show that the level of situational awareness decreases significantly in autonomous driving situations, especially when the *PS* is cognitively and attentively involved in an ancillary activity. As situational awareness requires time to be reactivated after the driver resumes driving, the *PS*'s careful handling of critical visual cues of the road environment will be altered, potentially resulting in an over-risk. The question to be solved here is twofold. On the one hand, how to detect and identify the loss of situation awareness of *PS* in the autonomous driving phase. This will undoubtedly be achieved by the ability to process physiological data from physiological sensors (oculometric, cardiac, electro-dermal) online. And, on the other hand, how to accompany the *PS* to regain situation consciousness when he lost it. This will involve the design of a smart Human System Interface (HSI, in following) informing the *PS* on elements related to the traffic for example, and interacting with him.

Autonomous driving and driving expertise

The switch cost associated with alternating is very sensitive to the nature of the processes implemented in the alternating tasks. Thus, the switch cost is all the more important as the processes involved require careful control, which is very costly in terms of workload. On the other hand, the switch cost associated decreases when the task requires less workload, and implements more automated processes. Like many human skills (reading, writing, lacing shoes, etc.), driving is a process that is first carefully controlled

and which, through a long and repeated training, becomes automatic. Today, the majority of drivers are considered as experts in driving activity (driving licence for more than 5 years, and 10,000 km driven per year at least). Nowadays, young drivers and older ones are over represented in the second category of un- and weakly- experimented drivers. Since the expertise of the driving activity is built through experience and repeated exposure to various driving situations, future autonomous vehicles will not *a priori* allow these drivers to maintain and/or increase their levels of road expertise. Thus, for the same number of kilometres travelled per year, the *PS* could never achieve sufficient driving experience to be considered an expert driver. Since the level of control that the subject exercises over alternating tasks or activities is a determinant of the cost of alternation, it seems essential to think an HSI of resumption aid for the most critical populations.

Research directions

Used of autonomous car simulators

As shown previously, one of the most critical issue to solve (after technological ones) is to ensure a safety HSI cooperation, which is finally the determinant of its acceptability for the human. One way to ensure the development of HSI responding to the needs and constrains of the human factors is to include the focused final user earlier in the design of the system. Announced for 2020 in 2016, it is noticeable that the autonomous car of level 3 and more is still a project. A mean to test *a priori* the safety in the HSI is the used of autonomous car simulators. They have the advantage 1) to offer the possibility to test every HSI solutions without any safety risk for the *PS* whatever their inner characteristics, 2) to put the *PS* in exactly the same critical contexts, ensuring to replicate the measures and 3), to be clearly less costly than road experiments with a "real" autonomous car.

Design and evaluation of interaction techniques

In such context, the amount of information the user may want to access is very large: it includes the real time information reflecting the current state of the car, road information such as speed limit or traffic jam ahead, navigation information related to a path predefined on a map but also information explaining to the driver the decision the car has just taken. Interacting with this large information environment to annotate, consult, filter, or even share information, necessarily needs the use of multiple commands. In traditional desktop contexts, reaching these commands would require large and deep menus and sub-menus, while observing this information would require large screens. In the context of the car, large screens are prohibited. In the literature, multi-display environments have been widely explored [4, 6, 32, 29]. More recently the concept of data physicalization [19, 7, 10] seeks to embed data into physical objects serving as referents to the information, and tangible interfaces allow shape-changing and flexible properties to touch screen devices providing eyes-free interaction in a cockpit [17]. Ultimately, on-body interaction has been explored to offer new supports for accessing multiple commands and data [30, 16]. All these alternatives are promising approaches to handle large information space and to access commands. There are however intrinsic constraints in the context of vehicle cockpit: small sizes of displays, luminosity, lack of horizontal surfaces, limited interaction space. These limitations must therefore be considered to revisit these approaches and compare their applicability and benefits.

Promote acceptability through argumentation techniques

In the context of automated driving, an important problem will be the notion of "acceptability" that is clearly related to the notion of explanation. Indeed, the *PS*'s trust will depend on the answer to the question: "why does the *AV*

take this decision?". Different approaches exist in literature, very often using explainable models (see for instance [20, 18]). These models are generally efficient but not formal and so it is very difficult to prove that they always give a good result. In another side, a complete formal theory exists that can be useful for producing explanations: the Argumentation Theory (see [11, 14]). So we think that the crossover of these two approaches will be interesting for solving our acceptability problem: argumentation theory could formally justify the behaviour of explainable models and also produce more readable explanations.

Conclusion

The goal of this position paper is to provide the automated driving and AI community, a clear view about the issues and the research directions regarding the problem of dynamic delegation between the driver and the vehicle in the case of autonomous vehicles (level 3 and 4). In order to deal with unexpected situations before and during the dynamic delegation phase, the Command System of the vehicle must ensure the integrity of information, such as robustness of different sources of data, information about the driver and the vehicle state and finally, the context and situational awareness. Adaptive and non-intrusive Human-Computer Interaction techniques must be designed and evaluated in order to provide the driver with customized and rapid control transition to the vehicle. These interaction techniques must have shape-changing and flexible properties and must be reinforced by several natural and multi-modal interaction mechanisms (speech, gestures, gaze and haptics). These multi-modal devices will be also used to alert the driver in case of critical situation or emergencies.

In addition, decision and collaboration capabilities are key factors that must be considered and characterized under different use cases for increasing safety and acceptability

of the driver. Most importantly, we have shown the notion of "acceptability" as a main issue to address in order to increase the driver's trust of the vehicle decisions. In this case, a proposed solution consists in designing and developing mechanisms based on Explainable Artificial Intelligence (XAI) models to inform clearly to the driver the automated decision of the vehicle related to the control transition to the driver. Together with advanced interaction technique, this will provide (1) explainable model and (2) explanation interface [25].

Finally, a future perspective is the exploration of cognitive models to understand the situational awareness, the reaction time, the emotional state and behavior of the driver in different use cases. These models will be also adapted to different characteristics and capabilities of the driver (mental or physical disabilities, age, genre, etc.) considering different situations and/or interaction scenarios.

REFERENCES

1. National Highway Traffic Safety Administration. 2014. J3016 Levels of Driving Automation Standard.
2. Saif Al-Sultan, Ali H. Al-Bayatti, and Hussein Zedan. 2013. Context-Aware Driver Behavior Detection System in Intelligent Transportation Systems. IEEE Transactions on Vehicular Technology 62, 9 (Nov 2013), 4264–4275. DOI: <http://dx.doi.org/10.1109/TVT.2013.2263400>
3. Mercedes Amor, Inmaculada Ayala, and Lidia Fuentes. 2010. A4VANET: Context-Aware JADE-LEAP Agents for VANETS. In Advances in Practical Applications of Agents and Multiagent Systems, Yves Demazeau, Frank Dignum, Juan M. Corchado, and Javier Bajo Pérez (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 279–284.

4. Louis-Pierre Bergé, Marcos Serrano, Gary Perelman, and Emmanuel Dubois. 2014. Exploring Smartphone-based Interaction with Overview+Detail Interfaces on 3D Public Displays. In Proceedings of the 16th International Conference on Human-computer Interaction with Mobile Devices & Services (MobileHCI '14). ACM, New York, NY, USA, 125–134. DOI : <http://dx.doi.org/10.1145/2628363.2628374>
5. Szymon Bobek and Grzegorz J. Nalepa. 2017. Uncertain context data management in dynamic mobile environments. Future Generation Comp. Syst. 66 (2017), 110–124.
6. Christophe Bortolaso, Matthew Oskamp, T.C. Nicholas Graham, and Doug Brown. 2013. OrMiS: A Tabletop Interface for Simulation-based Training. In Proceedings of the 2013 ACM International Conference on Interactive Tabletops and Surfaces (ITS '13). ACM, New York, NY, USA, 145–154. DOI : <http://dx.doi.org/10.1145/2512349.2512792>
7. Florent Cabric, Emmanuel Dubois, Pourang Irani, and Marcos Serrano. 2019. TouchGlass: Raycasting from a Glass Surface to Point at Physical Objects in Public Exhibits (regular paper). In IFIP TC13 Conference on Human-Computer Interaction (INTERACT 2019), Chypre, 02/07/2019-06/07/2019. Springer, <https://link.springer.com>.
8. Tom Carlson and Yiannis Demiris. 2012. Collaborative Control for a Robotic Wheelchair: Evaluation of Performance, Attention, and Workload. IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics) 42 (2012), 876–888.
9. Lemerrier Céline. 2017. Comprendre l'activité de conduite automobile pour mieux appréhender le rôle de la vision et de l'audition. Observatoire de la santé visuelle et auditive, Paris.
10. Maxime Daniel, Guillaume Rivière, and Nadine Couture. 2019. CairnFORM: A Shape-Changing Ring Chart Notifying Renewable Energy Availability in Peripheral Locations. In Proceedings of the Thirteenth International Conference on Tangible, Embedded, and Embodied Interaction (TEI '19). ACM, New York, NY, USA, 275–286. DOI : <http://dx.doi.org/10.1145/3294109.3295634>
11. Phan Minh Dung. 1995. On the acceptability of arguments and its fundamental role in nonmonotonic reasoning, logic programming and n-person games. Artificial Intelligence 77 (1995), 321–357.
12. M. Endsley. 1995. Toward a theory of situation awareness in dynamic systems. Human Factors 37(1) (1995), 32–64.
13. Mica R. Endsley. 2019. Situation Awareness in Future Autonomous Vehicles: Beware of the Unexpected. In Proceedings of the 20th Congress of the International Ergonomics Association (IEA 2018), Sebastiano Bagnara, Riccardo Tartaglia, Sara Albolino, Thomas Alexander, and Yushi Fujita (Eds.). Springer International Publishing, Cham, 303–309.
14. Xiuyi Fan and Francesca Toni. 2015. On Computing Explanations in Argumentation. In Proceedings of AAAI. 1496–1502.
15. Raul Fernandez-Rojas, Anthony Perry, Hemant Singh, Benjamin Campbell, Saber Elsayed, Robert Hunjet, and Hussein A. Abbass. 2019. Contextual Awareness in Human-Advanced-Vehicle Systems: A Survey. IEEE Access 7 (2019), 33304–33328. DOI : <http://dx.doi.org/10.1109/ACCESS.2019.2902812>

16. Bruno Fruchard, Eric Lecolinet, and Olivier Chapuis. 2018. Impact of Semantic Aids on Command Memorization for On-body Interaction and Directional Gestures. In Proceedings of the 2018 International Conference on Advanced Visual Interfaces (AVI '18). ACM, New York, NY, USA, Article 14, 9 pages. DOI : <http://dx.doi.org/10.1145/3206505.3206524>
17. David Antonio Gomez Jaureguay and Nadine Couture. 2019. Tacsell: Shape-Changing Tactile Screen applied for Eyes-Free Interaction in Cockpit. In Proceedings of the International Conference on Human Systems Integration (HSI'19). INCOSE, 8p.
18. Helen Hastie, Francisco J. Chiyah Garcia, David A. Robb, Atanas Laskov, and Pedro Patron. 2018. MIRIAM: A Multimodal Interface for Explaining the Reasoning Behind Actions of Remote Autonomous Systems. In Proceedings of ICMJ. 557–558.
19. Yvonne Jansen. 2014. Physical and Tangible Information Visualization. Ph.D. Dissertation.
20. Jinkyu Kim, Anna Rohrbach, Trevor Darrell, John Canny, and Zeynep Akata. 2018. Textual Explanations for Self-Driving Vehicles. In Proceedings of ECCV. 577–593.
21. D. LaBerge. 1983. Spatial extent of attention to letters and words. Journal of Experimental Psychology: Human Perception and Performance 9(3) (1983), 371–379.
22. Fagui Liu, Dacheng Deng, and Ping Li. 2017. Dynamic Context-Aware Event Recognition Based on Markov Logic Networks. In Sensors.
23. Clinton K. Brock J. Wilde G. Laurie I. Black D. Lonero, L. 1995. Novice driver education model curriculum outline. AAA Foundation for Traffic Safety, Washington.
24. Merat N. Louw, T. 2017. Are you in the loop? Using gaze dispersion to understand driver visual attention during vehicle automation. In Transp. Res. C, Emerg. Technol. Vol. 76. 35–50.
25. Prashan Madumal, Ronal Singh, Joshua Newn, and Frank Vetere. 2018. Interaction Design for Explainable AI: Workshop Proposal. In Proceedings of the 30th Australian Conference on Computer-Human Interaction (OzCHI '18). ACM, New York, NY, USA, 607–608. DOI : <http://dx.doi.org/10.1145/3292147.3293450>
26. Jamson A.H. Merat, N. 2008. ow do drivers behave in a highly automated car?. In Proceedings of the 5th International Driving Symposium on Human Factors in Driver Assessment, Training and Vehicle Design. 514–521.
27. Claus Möbus, Mark Eilers, and Hilke Garbe. 2011. Predicting the Focus of Attention and Deficits in Situation Awareness with a Modular Hierarchical Bayesian Driver Model. In Digital Human Modeling, Vincent G. Duffy (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 483–492.
28. Merat N. 2012. Highly automated driving, secondary task performance, and driver state. 5, Vol. 54.
29. Houssein Saidi, Marcos Serrano, Pourang Irani, and Emmanuel Dubois. 2017. TDome: A Touch-Enabled 6DOF Interactive Device for Multi-Display Environments. In Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems (CHI '17). ACM, New York, NY, USA, 5892–5904. DOI : <http://dx.doi.org/10.1145/3025453.3025661>

30. Housseem Eddine Saidi, Marcos Serrano, Pourang Irani, Christophe Hurter, and Emmanuel Dubois. 2019. On-Body Tangible Interaction: Using the Body to Support Tangible Manipulations for Immersive Visualization (regular paper). In IFIP TC13 Conference on Human-Computer Interaction (INTERACT 2019), Chypre, 02/07/2019-06/07/2019. Springer, <https://link.springer.com>.
31. David A. Sanders, Alexander Gegov, Giles Eric Tewkesbury, and Rinat Khusainov. 2019. Sharing Driving Between a Vehicle Driver and a Sensor System Using Trust-Factors to Set Control Gains. In Intelligent Systems and Applications, Kohei Arai, Supriya Kapoor, and Rahul Bhatia (Eds.). Springer International Publishing, Cham, 1182–1195.
32. Nicole Sultanum, Sowmya Somanath, Ehud Sharlin, and Mario Costa Sousa. 2011. "Point It, Split It, Peel It, View It": Techniques for Interactive Reservoir Visualization on Tabletops. In Proceedings of the ACM International Conference on Interactive Tabletops and Surfaces (ITS '11). ACM, New York, NY, USA, 192–201. DOI : <http://dx.doi.org/10.1145/2076354.2076390>